

Cat[®] Utility Compactors

APPLICATION GUIDE



Utility Compactor Application Guide

			0 - 1.8 Tons		1.8 - 3 Tons				3 - 5 Tons				
Material	Application	Layer Thickness mm (in)	CB14B and CB1.7	CB14B and CB1.8	CB22B and CB2.5	CB24B and CB2.7	CB24 XT and CB2.7 w/ballast	CC24B and CC2.6	CB32B and CB2.9	CB34B	CB36B	CC34B	
			900 mm (35")	1000 mm (39")	1000 mm (39")	1200 mm (47")	1200 mm (47")	1200 mm (47")	1200 mm (47")	1300 mm (51")	1300 mm (51")	1400 mm (55")	1300 mm (51")
Asphalt	Walking Paths, Driveways, Patchwork	25 - 50 (1 - 2)	Best	Best	Better	Better	Better	Better	Good	Good	Good	Good	
		50 - 100 (2 - 3)	Best	Best	Better	Better	Better	Better	Good	Good	Good	Good	
	Parking Lots, Urban Streets	25 - 50 (1 - 2)	Better	Best	Best	Best	Best	Best	Best	Best	Better	Better	Better
		50 - 100 (2 - 3)	Better	Better	Best	Best	Best	Best	Best	Best	Better	Better	Best
	Roads, Highways	25 - 50 (1 - 2)	Good	Good	Better	Better	Better	Better	Better	Best	Best	Best	Best
		50 - 100 (2 - 3)	Good	Good	Better	Better	Better	Better	Better	Better	Best	Best	Best
Soil	Landscaping	< 100 (4)	Best	Best	Better	Better	Better	Better	Good	Good	Good	Good	
	Small Job Sites	< 100 (4)	Best	Best	Better	Better	Better	Better	Good	Good	Good	Good	
	Medium Job Sites	< 100 (4)	Better	Better	Best	Best	Best	Best	Better	Better	Better	Better	

For more complete information on Cat products, dealer services, and industry solutions, visit us on the web at www.cat.com

Materials and specifications are subject to change without notice. Featured machines in photos may include additional equipment. See your Cat dealer for available options.

CAT, CATERPILLAR, their respective logos, "Caterpillar Yellow," the "Power Edge" trade dress as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.

QEXQ2348-01 4/18
© 2018 Caterpillar
All Rights Reserved

