

TRENCH & SHORING EQUIPMENT

WHEEL LOADERS

MODEL	HP	WEIGHT	BUCKET CAPACITY
908	84 hp	14,200 lb	1.4 yd³
914M	100 hp	19,315 lb	1.3 – 1.9 yd³
926	153 hp	28,770 lb	2.5 yd³
930K	154 hp	30,479 lb	3.0 yd³
938K	169 hp	35,104 lb	3.65 yd³
950K	211 hp	42,811 lb	4.0 yd³
962	250 hp	44,591 lb	3.3 yd³
966	276 hp	51,176 lb	4.19 yd³
972	299 hp	54,871 lb	4.19 yd³
980	386 hp	66,337 lb	5.25 yd³

*Forks

TELEHANDLERS

MODEL	RATED LOAD CAPACITY	MAX LIFT HEIGHT	MAX FORWARD REACH
TH255C	5,500 lb	18.3 ft	10 ft 8 in
TL542	6,500 lb	42 ft	30 ft
TL1055	10,000 lb	55 ft	42 ft 6 in
TL1255	12,000 lb	55 ft	42 ft 6 in
SkyTrak 6042	6,000 lb	41 ft 11 in	27 ft 11 in
SkyTrak 10054	10,000 lb	53 ft 2 in	38 ft 9 in
SkyTrak 12054	12,000 lb	53 ft 2 in	38 ft 10 in

Telehandler Attachments
Lift Hook, Material Handling Arm, Truss Boom

FORKLIFTS

MODEL	LIFT CAPACITY	POWER
2C6000	6,000 lb	Dual Fuel
GC45K	10,000 lb	Dual Fuel

VAC TRAILER

MODEL	HOSE LENGTH	VACUUM
LP800	30 ft	1000 cfm

PAVERS

MODEL	WEIGHT	AUGER DIAMETER	HP
P195	13,000 lb	12 in	67 hp
P265	16,200 lb	9 in	74 hp
P385	20,500 gal	12 in	100 hp

TANDEM VIBRATORY ROLLERS

MODEL	HP	WEIGHT	COMPACTION WIDTH
CB1.8	24.7 hp	3,825 lb	39 in
CB7	100 hp	19,015 lb	59 in
CB10	120 hp	21,638 lb	67 in
CB13	142 hp	27,557 lb	79 in

VIBRATORY SOIL COMPACTORS

MODEL	HP	WEIGHT	COMPACTION WIDTH
CS44	100 hp	15,961 lb	66 in
CP44	100 hp	16,832 lb	66 in
CG11GC	111.3 hp	24,769 lb	84 in
CP12GC	120.7 hp	27,869 lb	84 in

COMBINATION VIBRATORY ROLLERS

MODEL	HP	WEIGHT	COMPACTION WIDTH
CC24B	36.20 hp	5,380 lb	47 in
CC34B	48.8 hp	7,446 lb	51 in

PNEUMATIC ASPHALT ROLLERS

MODEL	HP	WEIGHT	COMPACTION WIDTH
CAT CW14	100.5 hp	28,528 lb	68 in
CW16	100.5 hp	11,464 lb	68 in

ALUMINUM TRENCH SHIELDS WITH END-LOADABLE SPREADERS

Manufactured from extruded aluminum panels, protection is provided for a wide range of depths and projects.

MODEL	DESCRIPTION	WEIGHT
XLAP-610	6’ x 10’ // 3” Wall	1,020 lb
XLAP-88	8’ x 8’ // 3” Wall	1,120 lb
XLAP-812	8’ x 12’ // 3” Wall	1,560 lb
Spreaders	36” – 60”	8 lb
Spreaders	48” – 72”	10 lb
Spreaders	52” – 88”	12 lb

STEEL TRENCH SHIELDS

Steel Trench Shields are designed to protect workers while on the jobsite. The combination of narrow sidewalls and good depth ratings allows for faster excavation and reduced labor time so you can get the job done quickly and more efficiently.

MODEL	DESCRIPTION	WEIGHT
XLD-416	4’ x 16’ // 4” Wall	4,130 lb
XLD-816	8’ x 16’ // 4” Wall	7,270 lb
XLD-620	6’ x 20’ // 4” Wall	7,220 lb
XLD-820	8’ x 20’ // 4” Wall	8,920 lb
HT6-624	6’ x 24’ // 6” Wall	10,210 lb
HT6-820	8’ x 20’ // 8” Wall	10,410 lb
HT6-824	8’ x 24’ // 6” Wall	12,290 lb
HT8-824	8’ x 24’ // 8” Wall	13,420 lb

HYDRAULIC VERTICAL SHORES

Designed to prevent cave-ins to the most unstable soil conditions, Hydraulic Vertical Shores provide support to the side walls of the trench through the use of hydraulic pressure. These safe, simple to use, and quick to assemble trench supports are designed to us be used as a spot bracing for repair situations or for production trenching.

MODEL	DESCRIPTION	WEIGHT
59423-RAW	Finn Form 4’ x 8’	75 lb
S-1 5X2236	22” x 36” Hyd Strut	20 lb
S-1 5X3455	34” x 55” Hyd Strut	25 lb
S-1 5X5288	52” x 88” Hyd Strut	30 lb

BEDDING BOXES

Bedding Boxes are built to hold a wide range of products and accommodate a variety of excavator buckets. The low 44” height profile allows for dump trucks to easily fill the box from either end or side.

MODEL	DESCRIPTION	WEIGHT
SM-5-D	Stone Mizer - 5 cubic yard	5,210 lb
SM-7.5-D	Stone Mizer - 7.5 cubic yard	6,120 lb
SM-9-D	Stone Mizer - 9 cubic yard (Wide)	6,890 lb
SM-12-D	Stone Mizer - 12 cubic yard (Wide)	8,590 lb

MANHOLE BOXES

Manhole Boxes are capable of being used in conjunction with Trench Shields to allow for little to no interruption on in-progress pipe jobs. The square configuration provides the needed inside clear span while reducing the amount of excavation and restoration work required.

MODEL	DESCRIPTION	WEIGHT
MHXLDW-410	4’ x 10’	3,215 lb
MHXLDW-810	8’ x 10’	5,840 lb
MHXLDW-412	4’ x 12’	3,650 lb
MHXLDW-812	8’ x 12’	6,860 lb

BUILD-A-BOX PANELS & CORNERS

Build-A-Box component panels, corner posts, and accessories can be transported in a pick-up truck, and easily assembled by hand into two, three, or 4-sided shielding configurations.

PANEL MODEL	WEIGHT	SHIELD CAPACITY
BBP-26 / BAB-6	8 lbs	2,400 PSF
BBP-28 / BAB-8	110 lbs	1,400 PSF
BBP-210 / BAB-10	135 lbs	950 PSF
BBP-212 / BAB-12	165 lbs	780 PSF
CORNER MODEL	LENGTH	WEIGHT
BBC-48	48 in	36 lbs
BBC-72	72 in	53 lbs
BBC-96	96 in	69 lbs

ROAD PLATES

With various sizes available, Road Plates are designed to provide safety for both vehicles and pedestrians when traveling over unstable terrain, trench covering, or street crossings.

MODEL	DESCRIPTION	WEIGHT
RP4X8	4’ x 8’ // 1” thick steel	1,344lb
RP4X12	4’ x 12’ // 1” thick steel	2,016 lb
RP8X8	8’ x 8’ // 1” thick steel	2,688 lb
RP8X12	8’ x 12’ // 1” thick steel	4,032 lb
RP8X20	8’ x 20’ // 1” thick steel	6,720 lb

AIKEN

(803) 220-2282

FLORENCE

(843) 678-8520

HILTON HEAD

(843) 784-6766

ROCK HILL

(803) 324-7667

SPARTANBURG

(864) 583-7667

COLUMBIA

(803) 754-7368

GREENVILLE

(864) 672-0400

MYRTLE BEACH

(843) 399-1692

SENECA

(864) 973-6767

SUMMERVILLE

(843) 875-5567



BlanchardMachinery.com



BLANCHARD RENTAL SERVICES

YOUR ONE STOP SHOP FOR ALL YOUR EQUIPMENT NEEDS.



833-4-EZRENT // BlanchardMachinery.com



BlanchardMachinery.com // 833.4.EZRENT



Scan code to view our full Rental Line Brochure!

RENTAL PRODUCTS

SCISSOR LIFTS

MODEL	PLATFORM HEIGHT	LIFT CAPACITY
1430	14 ft	500 lb
1930	19 ft	500 lb
2632	26 ft	500 lb
2646	26 ft	1,000 lb
3246	32 ft	700 lb
4069 DC	40 ft	800 lb
MODEL	PLATFORM HEIGHT	LIFT CAPACITY
GR20 Electric Runaround	20 ft	350 lb
MODEL	PLATFORM HEIGHT	LIFT CAPACITY
2668RT	26 ft	1,250 lb
3268RT	32 ft	1,000 lb

ARTICULATED BOOM LIFTS

MODEL	PLATFORM HEIGHT	HORIZONTAL REACH	LIFT CAPACITY
Z30/20N	30 ft	21 ft 5 in	500 lb
Z34/22N	34 ft	22 ft 3 in	500 lb
Z40/23N & Z	40 ft	22 ft 8 in	500 lb
Z45/25	45 ft	25 ft	500 lb
TZ-50	55 ft 6 in	29 ft 2 in	500 lb
Z60/34	60 ft	36 ft 6 in	500 lb
Z80/60	80 ft	60 ft	500 lb

*Call for specialty lifts.

STRAIGHT BOOM LIFTS

MODEL	PLATFORM HEIGHT	HORIZONTAL REACH	LIFT CAPACITY
S45	45 ft	36 ft 8 in	500 lb
S60X	60 ft	50 ft 10 in	1,000 lb
S65	65 ft	56 ft 2 in	500 lb
S85	85 ft	76 ft 6 in	500 lb
S125	125 ft	80 ft	500 lb

WELDER PRODUCTS

MODEL	
300/4000 Amp	Diesel
300 Amp	LPG

TRUCKS

MODEL	MAKE	TANK CAPACITY
WVT2000	Ford F500	2,000 gal
Dump Truck	Ledwell	5-7 yd
4K Gallon Water Truck		4,000 gal

FLOOR CARE

MODEL	MAKE	TYPE
T20	Tennant	Floor Scrubber
S20	Tennant	Floor Sweeper

TRAILERS

MODEL	PAYLOAD RATING	DECK HEIGHT	LOAD WIDTH
T-10HD Dump	10,000 lb	8 ft 6 in	82 in
T-5DT Dump	5,000 lb	12 in	77 in
Water Trailer	500 gal		

LANDSCAPING

MODEL	MAKE
Straw Blower	Turfmaker
Seeder	Turfmaker

GENERATORS

MODEL	WEIGHT	RUN TIME	OIL CAPACITY
15XR (15KW Gen)	3,160 lb	81.7 hrs	1.75

COMPACTION TOOLS

MODEL	WEIGHT	WORKING SPEED (MAX)
BT60 Jumping Jack	137 lb	81.7 hrs
BVP18/45 Plate Tamp	200 lb	82 ft/min
BMP8500 Trench Roller	3,516 lb	66 ft/min

BROOMS

MODEL	SIZE
Laymor	BHC (towable)
NV55	Ride-on Cab

LIGHT TOWERS

MODEL	OPERATING TIME	TOWER	LIGHTING
Allmand 30 NLV Lite Tower	76 hours	24 ft	1,250 watts

TRAFFIC CONTROL

MODEL	DESCRIPTION	POWER
Message Board	3-Line Message	Solar
Auto Flagger	Lights and Lift Arm	Solar

DINGO

MODEL	HP	WEIGHT
323 Wheeled Dingo	23 hp	1,567 lb
TX1000	24.9 hp	2,610 lb
TRX427	27 hp	2,075 lb

WORK TOOLS FOR TORO DINGO

- Trencher
 - Auger
 - Power Rake
- Forks
 - Leveler
 - Roto Dairon

AG TRACTORS

MODEL	HP	LIFT CAPACITY
TS6 130	112 hp	7,326 lb
TS6 110 Boom Mower	110 hp	3,735 lb
TS6 130 Batwing Mower	112 hp	7,326 lb
TS6 140	139 hp	7,326 lb
T6070	140 hp	12,185 lb
T8330	284 hp	15,183 lb

WORK TOOLS FOR AG TRACTORS

- Box Blade
 - Disc Harrow
- Rotary Tiller
 - Post Hole Digger

SITE DUMPER

MODEL	PAYLOAD	ENGINE PERFORMANCE
DV60	13,228 lb	74.2 hp

CONCRETE TOOLS

MODEL	OUTPUT POWER	MAX CUTTING DEPTH	WEIGHT
K770 (Chop Saw)	5 hp	5 in	22.4 lb
FS 400 LV (Flat Saw)	11.7 hp	7.5 in	220 lb
DMS 400 (Core Drills)	100-120 V	14 in	31 lb

ELECTRIC MACHINES

MODEL	RUN TIME	DIGGING DEPTH	
CMX18 Excavator	up to 8 hours	7.5 ft	
MODEL	RUN TIME	WIDTH	DUMP HEIGHT
ES800 High Tip Dumper	8+ hours	less than 35.5"	over 59"
2-speed Mini Skid Steer	8+ hours	less than 31"	over 6 ft

*We offer all models in between the specified listings above.

SKID STEER LOADERS

MODEL	HP	WEIGHT	LIFT CAPACITY/ TIPPING LOAD	WIDTH
232	65.8 hp	6,213 lb	1,850 lb / 3,700 lb	58.9 in
242D	73.2 hp	6,980 lb	2,150 lb / 4,300 lb	66 in
246D	72.9 hp	7,424 lb	2,150 lb / 4,300 lb	66 in
262D	72.9 hp	8,011 lb	2,700 lb / 5,400 lb	66 in

COMPACT TRACK LOADERS

MODEL	HP	WEIGHT	LIFT CAPACITY/ TIPPING LOAD	WIDTH
239	67.1 hp	7,434 lb	1,530 lb	69 in
249D	65.8 hp	7,685 lb	2,300 lb / 4,600 lb	69 in
259D	73.2 hp	8,945 lb	2,900 lb / 5,800 lb	69 in
279D	72.9 hp	9,893 lb	2,935 lb / 5,870 lb	78 in
289D	72.9 hp	10,533 lb	3,800 lb / 7,600 lb	78 in
299D XHP	95 hp	11,612 lb	4,250 lb / 8,500 lb	78 in

SKID STEER / COMPACT TRACK LOADER WORK TOOLS

- Cold Planer
 - Forks
 - Auger
 - Multi Purpose Buckets
- Mower Decks
 - Angle Broom
 - Pick Up Broom
- Grapples
 - Hammers
 - Trenchers
- Landscape Tillers
 - Harley Rakes

BACKHOE LOADERS

MODEL	HP	WEIGHT	DIGGING DEPTH
415F	68 hp	24,251 lb	14 ft 3.6 in
416F	87 hp	14,881 lb	14 ft 3.6 in
420F	93 hp	15,201 lb	14 ft 3.6 in
420F IT	93 hp	15,201 lb	14 ft 3.6 in

*Hammers available

MINI EXCAVATORS

MODEL	HP	WEIGHT	DIGGING DEPTH	WIDTH
300.9D	13 hp	2,061 lb	5 ft 8 in	2 ft 4.8 in
303	23.5 hp	7,782 lb	9 ft	5 ft
303.5E CR	31.6 hp	8,139 lb	9 ft 6 in / 10 ft 4 in	5 ft 10 in
304	45 hp	9,867 lb	138.2 in	6 ft 4 in
305E CR	40.2 hp	11,217 lb	10 ft 9 in / 12 ft 1 in	6 ft 6 in
308E2 CR SB	65 hp	18,519 lb	13 ft 7 in / 15 ft 5 in	7 ft 7 in
309 Hammer/ Mower Machine	74.3 hp	9,867 lb	182 in	8 ft 1 in

*Digging Depth with standard/long stick

EXCAVATORS

MODEL	HP	WEIGHT	DIGGING DEPTH	REACH
313FGC	70 hp	29,800 lb	19 ft 9 in	28 ft 3 in
312E	91 hp	33,080 lb	19 ft 10 in	27 ft 8 in
315	97 hp	37,794 lb	19 ft 6 in	28 ft 6 in
316E	113 hp	38,801 lb	21 ft 7 in	29 ft 6 in
320E L	153 hp	54,450 lb	24 ft 10 in	30 ft 6 in
320E LRR	153 hp	56,440 lb	22 ft 1 in	32 ft 4 in
323F	161 hp	50,900 lb	22 ft 1 in	32 ft 4 in
325F	172 hp	49,604 lb	22 ft	32 ft 1 in
326F	201 hp	57,100 lb	22.38 ft	33 ft
326F Long Reach	204 hp	58,470 lb	48 ft 4 in	60 ft 6 in
330	273 hp	68,100 lb	23 ft 8 in	35 ft 1 in
330F Long Reach	273 hp	68,200 lb	47 ft 11 in	59 ft
336E L	300 hp	86,200 lb	24 ft 7 in	36 ft 2 in
336E H Hybrid	286 hp	82,000 lb	24 ft 7 in	36 ft 2 in
349E L	396 hp	117,500 lb	26 ft 10 in	39 ft 9 in

*Hydraulic Thumbs available

EXCAVATOR HAMMERS

MODEL	ENERGY CLASS	MACHINE CAPABILITY	BLOWS PER MINUTE
H25D	150 ft-lbf	300.9	1,900
H55	600 ft-lbf	246D	600 – 1,680
H120	3,000 ft-lbf	(315 – 329)	350 – 620

TRACK-TYPE TRACTORS

MODEL	HP	WEIGHT	BLADE WIDTH	BLADE CAPACITY
D1	74 hp	17,004 lb	9 ft 1.5 in	2.59 yd³
D3 XL	104 hp	20,534 lb	9 ft 1.5 in	2.85 yd³
D3 LGP	104 hp	21,256 lb	10 ft 6.7 in	3.05 yd³
D4 XL	130 hp	29,346 lb	10 ft 6 in	4.01 yd³
D4 LGP	130 hp	30,750 lb	12 ft	4.38 yd³
D5 XL	150 hp	36,392 lb	10 ft 4.2 in	4.16 yd³
D5 LGP	150 hp	39,895 lb	13 ft 4.68 in	4.13 yd³
D6 XL (VPAT)	230 hp	52,157 lb	12 ft 9.6 in	6.19 yd³
D6 LGP (VPAT)	230 hp	53,551 lb	13 ft 8.4 in	5.5 yd³
D8 STD	317 hp	87,733 lb	12 ft 10.8 in	11.4 yd³

ARTICULATED TRUCKS

MODEL	HP	RATED PAYLOAD	WEIGHT (EMPTY)
725C	314 hp	26 tons	51,191 lb
730C	367 hp	31 tons	53,131 lb
745	740 hp	45.2 tons	73,634 lb
912HM Hydrema Truck	131 hp	11 tons	19,047 lb
922HM	296 hp	20 tons	32,800 lb
740 Water Truck		4,000 gal	

MOTOR GRADERS

MODEL	HP	WEIGHT	BLADE
120M2	145 hp	39,892 lb	12 ft
12M	173 hp	33,064 lb	12 ft
140M	183 hp	41,868 lb	12 ft
140M2	193 hp	43,686 lb	12 ft

